

P02021 : PREMAC SUPER FLOOR POLISH

PREMAC SUPER FLOOR POLISH	P02021
---------------------------	--------

description	A fully buffable, wax rich emulsion floor polish for the treatment of vinyl, linoleum, rubber, sealed wood and waxed wood floors.
directions	DIRECTIONS For further information on stripping, rejuvenation and application techniques please refer to Technical Information Sheet. • Prepare floor using suitable emulsion polish stripper (Premstrip 2000 or Strike) or multi-purpose detergent (MP9 or MP10) following product directions • Apply a thin even coat of neat polish using a clean mop or applicator • Allow polish to dry (30 – 40 minutes) • Apply second coat at right angles to the first leaving a 10cm gap around the edges • Allow a minimum of four hours after application of final coat for the polish film to fully cure and harden MAINTENANCE • Maintain polish film using a maintenance product (Clean & Buff or Reflect Maintainer) following product instructions • Premac Super is suitable for spray burnishing when diluted at 1:10

Technical	
-----------	--

Product is for professional use only.

SELDEN RESEARCH LIMITED, STADEN BUSINESS PARK, BUXTON, DERBYSHIRE, SK17 9RZ T: 01298 26226 F: 01298 26540 E: SALES@SELDEN.CO,UK