Numete

TECHNICAL SHEET

Trade Line (M-Class)

Nome	
Name	TRM 240H
Reference	915233
EAN code	5028965868355
Power supply	
Power supply type	230v AC 50/60Hz
Rated Motor Power	620W
Protection class	Class II
Airflow Motor only	48 L/sec
Max Sealed Suction H ² 0	2300mm
Max Air Flow (Motor Only)	173 m3/h
Max Air Flow (In Product)	115 m3/h
MAX Under Pressure	220 (hPa)
Sound Pressure (LpA)	70 dB (A)
Uncertainty (KpA)	2 dB
Cable length	10m
Cleaning Range	32m
Cable Type	HO5VV-F
NUPLUG system	No
Capacity / Weight Size	
Drum Capacity (DRY)	9L
Weight (Ready to Work)	8.1kg
Packed Weight	9.48kg
Width	360mm
Length	360mm
Height	390mm
Filtration	
Type M to (BS EN 60335-2-69)	M CLass
Filter Type (918048 Cartridge)	H14
Hepa Dust Bag	NVM-1CH
Filter	TriTex
Kit AS76	
914762 2.8M Parallel Hose Assembly (32MM)	
900918 MFB 300 32MM MultiFlo Brush 300MM Floor Nozzle	
601008 32MM Stainless Steel Extension Tube	
601052 32MM Stainless Steel Tube Bend Black NPC Volume Control	
217067 - 38MM/23MM Adaptor	
601141 - 32MM Double Taper Adaptor	
601144 - 65MM Soft Dusting Brush	
601142 - 32MM Crevice Tool	
604165 TriTex Filter for 305mm Machine	



M-Class DRY VACUUM

TheTRM240 has a Washable H14 Filter, 3 Levels of Filtration, 2.8M Long-Reach Hose, Rewind Cable Storage, 10M Hi-Vis Cable

Delivering outstanding performance, value and reliability with M-Class filtration.



Advanced Filtration M-Class compliant, the long-life and washable HEPA filter provides the most advanced filtration of 99.995% at 0.3 microns.

Built to Last Made for tough with long-life 620W motor proven to last many,

many years.

Powerful & Efficient Patented AirFlo technology brings exceptional performance.

Ease of Transit Compact size, the TRM240 is easily stored and manoeuvred from van to site.

A Tool for Every Job Professional and versatile AS76 accessory kit and Stainless Steel tube set.



Specification subject to change without prior notice